

OCXO (Oven Controlled Crystal Oscillators) OC149E3A, OC149E3S Series

+3.3 V
Sine Wave



MERCURY
Since 1973

Features:

- Full size 4 pin DIP full metal package
- +3.3 V D.C supply Voltage
- 50 ohm load Sine wave output
- Choice of AT-cut or SC-cut crystal
- Voltage control (Electronic Frequency Tuning) on pin 1



General Specifications:

Output Wave From		Sine wave. Wave form code is "E"	
Frequency Range		AT-cut crystal: 8.0 MHz ~125.0 MHz SC-cut crystal: 10.0 MHz ~ 100.0 MHz	
Type of Crystal Cut Used		AT -cut. Use "A" for crystal code. SC -cut. Use "S" for crystal code Please refer to technical note TN031 for SC and AT-cut crystal comparison	
Supply Voltage (V_{DD})		+3.3 V (voltage code is "3")	
Initial Calibration Tolerance		AT-cut: ±0.5 ppm max. at the time of shipment. @ +25°C, Vcon = +1.65 V SC-cut: ±0.05 ppm max. at the time of shipment. @ +25°C, Vcon = +1.65 V	
Frequency Stability vs	Operating Temperature Range (custom spec. on request)	AT-cut crystal	SC-cut crystal
		±0.05 ppm over -20°C to +70°C	±0.02 ppm over -20°C to +70°C
		±0.1 ppm over -20°C to +70°C	
		±0.3 ppm over -20°C to +70°C	
	Long Term Aging	±0.1 ppm over -40°C to +85°C	±0.05 ppm over -40°C to +85°C
		±0.5 ppm over -40°C to +85°C	
Voltage Control on pin 1	Supply Voltage ±5% Variation		AT-cut: ±30 ppb typical ; SC-cut: ±20 ppb typical
	Load ±5% variation		AT-cut: ±30 ppb typical ; SC-cut: ±20 ppb typical
	Electronic Frequency Control (EFC at pin 1)		AT-cut: ±5.0 ppm typical; SC-cut: ±1.0 ppm typical
	Control Voltage Range		0.3 V to 3.0 V
	Transfer Function		Positive: Increasing control voltage increases output frequency
	Input Impedance		100 K Ω min.
Power	EFC Linearity		±10% max.
	Power Dissipation	Steady-state: 250 mA max. at +25°C.	
		Warm-up: 650 mA max.	
Output	Warm-up time (at +25°C)		AT-cut: 3 minutes max. Within ±0.1 ppm of the unit output frequency. SC-cut: 2 minutes max. Within ±0.1 ppm of the unit output frequency.
	Output Wave Form		Sine Wave
	Output Load		50 Ω typical
	Output Level		5 dBm min.
Harmonic Attenuation		-25 dB max.	

MERCURY www.mercury-crystal.com

Taiwan: TEL (886)-2-2406-2779, FAX (886)-2-2496-0769, e-mail: sales-tw@mercury-crystal.com

U.S.A.: TEL (1)-909-466-0427, FAX (1)-909-466-0762, e-mail: sales-us@mercury-crystal.com

“ O C X O ”


Oven Controlled Crystal Oscillators **Wave Form: TTL / CMOS Square Wave**



MERCURY
Since 1973

	Spurious Attenuation		-75 dB max.			
	Phase Noise	Offset	10 Hz	100 Hz	1 KHz	10 KHz
		10 MHz AT-cut Crystal	-80 dBc typ.	-120 dBc typ.	-145 dBc typ.	-150 dBc typ.
Storage Temperature			-40°C to +85°C			
Shock			2000 G's, 0.3 ms ½ sine			
Vibration			10 to 2000 Hz / 10 G's			

OC149E3 Test Circuit:




OC149E3 Package Dimensions and Pin Connections:

unit mm [inches]

Pin 1: Voltage Control Pin 7: Ground / Case
 Pin 8: Output Pin 14: Supply Voltage

Square corner is pin No. 1



Part Number Format and Example:

Example: OC149E3A-10.000-0.1/-20+70

OC149E3	A	—	10.000	—	0.1	/	-20+70
①	②	dash	③	dash	④	slash	⑤

①: OC149E3: OC149 series; “E” for 50 ohm load sine wave; “3” for +3.3 V supply voltage

②: Crystal type. “A” for AT-cut crystal; “S” for SC-cut crystal ③: Frequency in MHz

④: Frequency stability in ppm ⑤: Operating temperature range in Celsius